

Model  
**ECOLIFT 1.5**  
LOW-LEVEL ACCESS



## We call it 'Non-Powered, Powered Access.'

Battery and electric power free, the Ecolift 1.5 is elevated by simply and easily rotating the handle; the patented lift mechanism glides you smoothly to your chosen working height in seconds.

With no batteries (to charge and look after) and no hydraulic oil the Ecolift 1.5 is truly an Eco friendly solution. Its tiny footprint and simplicity of use finally provides a purely mechanical solution that doesn't involve erecting, unfolding or climbing.



### Key Features

- Intuitive to operate - turn handle to elevate
- Patented\* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (985mm x 700mm)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

### **PUSH AROUND - Self Powered**

Indoor Use

**Working Height:** 3.5 m

**Applications:** Pipe Work,  
M&E. Cleaning. Painting.  
Retail. FM.

# Model ECOLIFT 1.5

LOW-LEVEL ACCESS

## Specifications

### WORKING DIMENSIONS

Maximum working height:	3.50m
Maximum platform height:	1.50m
Basket dimensions:	720mm (L) x 600mm (W)
Working footprint:	985mm x 700mm
Safe working load:	150kg (1 person + tools)
Maximum manual force:	200N
Maximum gradient for operation:	0 degrees
Maximum wind force:	Internal use only, 0 (zero) mph
Maximum wheel force:	125kg
Maximum castor point load:	125kg (1.23kN)
Sound pressure level:	Less than 70DbA

### CLOSED DIMENSIONS

Length:	985mm
Width:	700mm
Height:	1.55m
Weight:	180kg

LIFT CYCLES Unlimited

## Safety features

- Auto-braked on entering basket
- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked



## IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.

# JLG®

## JLG EMEA BV

Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Tel: +31 (0)23 565 5665  
Fax: +31 (0)23 557 3750  
[www.jlg.com](http://www.jlg.com)

An Oshkosh Corporation Company